



BANCE



SMITHLIGHT MODEL INI20LR

NR CATALOGUE NUMBER: 0054/039168
LU CATALOGUE NUMBER: Plant/9238



Also available as Intrinsically Safe (Model EX90L) for explosive environments. IECEx, Zone 0 Group I, Group IIA T2 IP65. Please contact us for details.

- **Robust solid construction manufactured from ABS747IP65**
- **Shock absorbing rubber fitted to base, rubber seal on lid**
- **UV and saltwater resistant**
- **2 directional independent light heads or dual direction**
- **60° angle directional light positioning**
- **Adjustable height light head**
- **Generates no (or very little) heat**
- **Special base to allow fitting of a range of fixing accessories, e.g. scaffolding bracket, harness, tripod etc.**
- **Low battery warning**
- **Mains charger and vehicle charger**
- **Battery, chargers and light unit all contained within easy to carry robust case**

R. BANCE & CO. LTD.

Cockcrow Hill House, St. Marys Road, Surbiton, Surrey KT6 5HE, UK

Tel: +44 (0)20 8398 7141 Fax: +44 (0)20 8398 4765 e-mail: admin@bance.com URL: www.bance.com

BANCE

Fixing Accessories



Scaffolding Bracket



Adjustable Strap



Square Bracket



Tripod

Specification

Weight: 7.7 kg
Open Height: 1120 mm
Closed Height: 600 mm
Width: 334 mm
Depth: 220mm

Charging

240v AC Mains Charger
12/24v DC Vehicle Charger
Recharge in 7 - 8 Hours

Features

1 hour remaining warning light and sounder

10,000 hours (approx) battery life

Operation

10 - 12 hours continuous use with one light head

5 - 6 hours continuous use with two light heads

2 adjustable height levels

2 directional light options or dual direction option



R. BANCE & CO. LTD.

Cockcrow Hill House, St. Mary's Road, Surbiton, Surrey KT6 5HE, UK

Tel: +44 (0)20 8398 7141 Fax: +44 (0)20 8398 4765 e-mail: admin@bance.com URL: www.bance.com